



# VTechCS6719-16 Button Replacement

This is a guide that locates and replaces the inner buttons of the phone.

Written By: Charles montes



## INTRODUCTION

This guide demonstrates a walk-through of steps needed to completely dismantle the phone in order to locate the buttons and replace them with new ones.

---



### TOOLS:

- [Phillips #0 Screwdriver](#) (1)
  - [Metal Spudger](#) (1)
-

## Step 1 — Buttons



- Remove the sliding back cover from case.

## Step 2



- lift the battery and unplug the two pin cable from phone base.

## Step 3




- Remove the two 10mm screws at the base of the phone .

## Step 4



- ⚠ Use the spudger along the edge using a firm but gentle lifting motion.
- ⓘ When doing this feel for the hooks that latch the phones front and back cases.

## Step 5



- Unscrew a second set of 10mm screws to obtain access to the other side.


## Step 6



- *i* The front of the phone can now be placed to the side
- You will notice the button covers, these display the numerical values and positions of each button
- These can be placed aside as they will get in the way later.



## Step 7



- ❗ Now the silicon pads for the phone buttons are exposed.
- These can easily be removed by pulling away the pads from the circuit board.
- To replace simply align the new pad onto the button positions.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-08-09 11:51:03 AM.